
TOYOTA
TOYOTA
USL
USL
USL
SCRAP


TOYOTA
TOYOTA
RITCHIE BROS.
Auctioneers


USF Reddaway
USF
STORAGE
TOYOTA
TOYOTA
80578


YANMAR
TOYOTA
RITCHIE BROS.
Auctioneers


40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
RITCHIE BROS.
Auctioneers


RITCHIE BROS.
Auctioneers


TOYOTA
RITCHIE BROS.


rb BITCHIE BROS.
Auctioneers


RITCHIE BROS.
Auctioneers




533/178-381


16X6X10½


406/127-266.7






TOYOTA MATERIAL HANDLING
70032
S/N: 319CS 85619 MODEL: 1050EC3-18S-HE
SPEC: 501165-001 BCI CODE: 100D6C8
- DC OUTPUT PER CIRCUIT -
BATTERY TYPE: LA NO. CIRCUITS: 1
NO. CELLS: 18
AMP HOURS: 125 TO 1050 IN 8 HOURS
VOLTS: 12/24/36
MAX. AMPS: 171 CSA CERTIFIED AT:
- AC INPUT -
VOLTS: 480 PHASE: 3 HZ: 60
MAX AMPS: 10.3
AMETEK PRESTOLITE POWER
TROY, OH 45373
C
BC
c UL us
LISTED


TOYOTA MATERIAL HANDLING
80508
AUTHORIZED SALES & SERVICE
STAR TAM, INC.
888-750-2061
FAX: 510-351-5385
www.startam.com
INDUSTRIAL BATTERIES & CHARGERS
PROPOSITION 65 WARNING:
Battery posts, terminals and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and reproductive harm. Batteries also contain other chemicals known to the State of California to cause cancer. WASH HANDS AFTER HANDLING
Deka
BATTERY TYPE 18 – D85 – 25
NOMINAL VOLTAGE 36
SERIAL NUMBER 4096CK
RATED 6 HR. A.H. CAPACITY 1020
FULL CHARGE SPECIFIC GRAVITY 1.280 – 1.295
FINISH RATE, AMPS 51
MAXIMUM CHARGE RATE
EAST PENN manufacturing co., inc.
LYON STATION, PA 19536
Made in U.S.A.
AS TO FIRE AND ELECTRIC SHOCK HAZARD ONLY.
STORAGE BATTERY TYPE "E" (WITH COVER)
OR TYPE "EO" (WITHOUT COVER)
FOR USE IN INDUSTRIAL TRUCKS
173F
RITCHIE BROS.


TOYOTA
80578
80508
Deka


TOYOTA
80578
Deka
RITCHIE BROS.
Auctioneers


TOYOTA
TOYOTA
YANMAR
RITCHIE BROS.
Auctioneers


TOYOTA
TOYOTA
YANMAR
RITCHIE BROS.
Auctioneers

[2] In any of the following cases, stop operation and ask TOYOTA dealer for inspection:
- "TO OPERATING POSITION!" is not indicated when operator is off operating position.
- "TO OPERATING POSITION!" is indicated when operator is on operating position.
- Mark is indicated on display, and it is not turned off when operator returns to operating position after leaving it once.

(ENGLISH) 57914-U1169-71

MAKE SURE THE CATCH IS FIRMLY LOCKED.

MAKE SURE THE CENTER HOOK IS FIRMLY LOCKED.

BATTERY HOOD

57824-U1161-71

TOYOTA ELECTRIC FORKLIFT TRUCK

MODEL	8FBCU25			SERIAL NO.	85353
MAST	FSV	BACK TILT	5	ATTACH	SIDE SHIFTER
TYPE	E	VOLTAGE	36 V	BATTERY TYPE	E D
FRONT	35 in	TIRE SIZE FR	21X7X15/SOLID		
TREAD	890 mm	TIRE SIZE RR	16X5X10-1/2/SOLID		
TRUCK WEIGHT W/O BATTERY ACCURACY ±5%	7280 lb	BATTERY WEIGHT MIN/MAX	2400 lb / 3154 lb		
	3300 kg		1090 kg / 1430 kg		

RATED CAPACITY WITH VERTICAL MAST EQUIPPED AT MAX. LIFT HEIGHT AT AS SHOWN

	A	B	C	D	CAPACITY
in	24	24	189	0	4400 lb
	600	600	4800	0	2000 kg
in	30	30	189	0	3870 lb
	760	760	4800	0	1740 kg

THIS FORKLIFT TRUCK MEETS OR EXCEEDS DESIGN SPECIFICATIONS OF ANSI B56.1 IN EFFECT ON THE DATE OF MANUFACTURE

WARNING IMPROPER OPERATION OR MAINTENANCE COULD RESULT IN INJURY OR DEATH. TRAINED OPERATORS ONLY. READ OPERATOR'S MANUAL FIRST.

WARNING

BREAKING THESE RULES WILL CAUSE DEATH OR SERIOUS INJURY TO YOU

- Do not operate this truck unless your employer says you are t
- Read the Operator Manual before you start this truck. If it is missing or you do not understand it, ask your employer
- Lift trucks must be inspected every shift (See Operator Manual). Do not try to operate a truck that needs repairs or try to fix it yo Report all problems to your employer.
- Never lift or carry riders on forks or on truck. The mast can lower controlled or maintained properly.
- Learn and follow your employer's safety rules for operation, traffi Look where your truck is going to avoid people, obstructions, and Check clearances in all directions, including overhead. Travel in reverse if the load blocks your view.
- Never turn, park, or stack loads on slopes. Travel them with loads u for slippery surfaces.
- Lift trucks can tip over even when empty. Slow down for turns, steer slowly. Always fasten the seatbelt and stay with the truck if it tips
- Keep under the overhead guard. Do not lift over capacity loads or unb Keep forks low and tilted back. Carry long, high or wide loads slowly.
- Park only in authorized places. Before getting off truck, lower the forks attachments to the floor, put drive in neutral, turn off key, and set park

(ENGLISH) 57

Operator p (OPSS).

OPSS restric hydraulic fun operator leave

Lift trucks with than similar lift

Refer to Operato additional operati

Failure to follow op may result in death

RITCHIE BROS. Auctioneers


KEY ON 3377.3 h
LAP 3377.3 h
2 SEC
RESET
NEXT
MENU
RITCHIE BROS.
Auctioneers


SAS
SYSTEM OF ACTIVE STABILITY
RITCHIE BROS
Auctioneers


SAS
STABILITY