



FRITCHIE BROS.













TOYOTA

FB RICHIE BROS.  
Auctioneers



© 2014 RICHIEBROS





rowland.com



© 2014 Hyster































**FORKLIFT TRUCK**

14416  
OPERATOR  
LID  
D

MAX. LIFT HEIGHT "A" AS SHOWN	
3000	lb
1360	kg
3000	lb
1360	kg

THIS FORKLIFT TRUCK  
MEETS OR EXCEEDS DESIGN  
SPECIFICATIONS OF ASME/  
ANSI B56.1 IN EFFECT ON  
THE DATE OF MANUFACTURE.

**MAINTENANCE COULD RESULT  
IN DEATH OR SERIOUS INJURY TO  
OPERATORS ONLY.**  
57846-U2172-71















**bruce**  
AUC





(mm) - 4000 PSI (SI)















VECS

322

DANGER/POISON  
READ THIS LABEL CAREFULLY  
FOR YOUR PROTECTION  
AND THE PROTECTION OF OTHERS  
KEEP THIS LABEL ON THE BATTERY  
UNTIL YOU ARE THROUGH WITH IT  
DO NOT REMOVE THIS LABEL  
UNLESS YOU ARE TO REMOVE IT  
FOR REPAIR OR MAINTENANCE  
OR TO REPLACE THE BATTERY  
WITH ANOTHER BATTERY  
OF THE SAME TYPE AND  
CAPACITY AS THE ORIGINAL  
BATTERY

ROBITCHIE BROS.  
AUTOMOTIVE

1122





AVOID EYES  
EXPLOSIVE  
GASES CAN CAUSE  
BURNINGS OR INJURY

3722

RD  
E  
112

Model-825

FBRI  
Auction





COYOTA  
**4Y ECS**

**EMISSION CONTROL INFORMATION**



THIS ENGINE COMPLIES WITH U.S. EPA AND CALIFORNIA REGULATIONS FOR 2004 LIGHT-DUTY HIGHWAY SI ENGINES. EMISSIONS WARRANTY LIMITED APPLICATIONS ONLY.

**THIS ENGINE IS CERTIFIED TO OPERATE ON LPG & GASOLINE**

ENGINE FAMILY 91E80Z 204Y  
DISPLACEMENT 2.237 L/PIERS  
MAX POWER (kW/rpm) 38/2570 (L), 38/2570 (G)  
MAX SPEED 2570 rpm

**NO OTHER ADJUSTMENTS NEEDED**

SPARK PLUG GAP 0.7 - 0.8mm  
FIRING ORDER 1-3-4-2  
IGNITION TIMING F° BTDC (750 rpm)

TWC, HC/PS, MP/L, NA

112/98-02213-21

EMISSION STANDARDS  
CO 20 g/kwh  
HC+NO<sub>x</sub> 0.52 g/kwh

55





1000000-01  
WILLIAMS PARTS  
MANUFACTURING CO.  
M

(70Y007A-G05E1)

AST1669 / A-WP70KPA-2006

FITCHE BROS.  
INC.














TOYOTA



# TOYOTA FORKLIFT TRUCK

MODEL	BF6CU15		SERIAL NO.	14416	
MAST TYPE	FSU	BACK TILT	5	ATTACH	SIDE SHIFTER
FRONT TREAD	31.3 in	TIRE FR SIZE	18x6x12-1/8/SOLID		
	798 mm	TIRE RR SIZE	14x4-1/2x8/SOLID		
TRUCK WT.	6540	lb			
ACCURACY±5%	2970	kg			

RATED CAPACITY WITH VERTICAL MAST EQUIPPED AT MAX. LIFT HEIGHT "A" AS SHOWN



	A	B	C	CAPACITY	
in	217.5	24	0	2300	lb
mm	5535	600	0	1050	kg
in	217.5	30	0	2000	lb
mm	5535	760	0	900	kg

THIS FORKLIFT TRUCK  
MEETS OR EXCEEDS DESIGN  
SPECIFICATIONS OF ASME/  
ANSI B56.1 IN EFFECT ON  
THE DATE OF MANUFACTURE.



## WARNING

IMPROPER OPERATION OR MAINTENANCE COULD RESULT  
IN INJURY OR DEATH. TRAINED OPERATORS ONLY.  
READ OPERATOR'S MANUAL FIRST.

57846-U2172-71

H  
F



8393.6h



FB RICH BROS.



# TOYOTA FORKLIFT TRUCK

MODEL	8FECU15		SERIAL NO.	14416
MAST TYPE	FRONT	BACK TILT	5	
ATTACH	SIDE SHIFTER			
FRONT TREAD	in	TIRE FR SIZE	18x8x12-1/2/SOLID	
	mm	RR SIZE	14x4-1/2x8/SOLID	
TRUCK WT.	6540	lb		
ACCURACY±5%	2970	kg		

RATED CAPACITY WITH VERTICAL MAST EQUIPPED AT MAX. LIFT HEIGHT "A" AS SHOWN



	A	B	C	CAPACITY	
in	217.5	24	0	2300	lb
mm	5535	600	0	1050	kg
in	217.5	30	0	2000	lb
mm	5535	760	0	900	kg

THIS FORKLIFT TRUCK MEETS OR EXCEEDS DE SPECIFICATIONS OF ANSI B56.1 IN EFFECT ON THE DATE OF MANUFAC

**WARNING** IMPROPER OPERATION OR MA IN INJURY OR DEATH. TRAIN READ OPERATOR'S MANUAL



West Michigan  
**FORKLIFT**

DATE SERVICE HOURS

DATE	SERVICE	HOURS
7-24-16		6476
8-20-16		6616
9-21-16		6933
12-16-16		7009
9-15-17		7338
10-20-17		7392
7-2-18		75037E
12-12-18		7800
4-11-19		8208



480000000

OC S&HP Tag

**\$75-36**

Lot #

Serial

**4416**

200   
Water   
Refrigerator

Floods   
Inspection

NAS

**ATA**





TOYOTA











6TX - 3/8" (9.5 mm) - 4000 PSI WP (276 BAR) - SAE100R16 2 WIRE MSMAIC-189  
3/8" (9.5 mm) - 4000 PSI WP (276 BAR) - SAE100R16 2 WIRE MSMAIC-189  
3/8" (9.5 mm) - 4000 PSI WP (276 BAR) - SAE100R16 2 WIRE MSMAIC-189















RECHIEBROS.